

LED Moving / Static Message Display

LED MOVING / STATIC MESSAGE DISPLAY

MODEL	Pixel details		CABINET size approximately.						Either	Or
			in MM			in INCHES			Maximum lines in English (50mm to 60mm high)	Maximum lines in Vernacular (120 mm to 140mm)
	High	Wide	HEIGHT	WIDE	DEEP	HEIGHT	WIDE	DEEP		
FOS-11	16	32	250	410	95	9.8	16.1	3.7	2	1
FOS-12	16	64	250	730	95	9.8	28.7	3.7	2	1
FOS-13	16	96	250	1050	95	9.8	41.3	3.7	2	1
FOS-14	16	128	250	1370	95	9.8	53.9	3.7	2	1
FOS-15	16	160	250	1690	95	9.8	66.5	3.7	2	1
FOS-16	16	192	250	2010	95	9.8	79.1	3.7	2	1
FOS-17	16	224	250	2330	95	9.8	91.7	3.7	2	1
FOS-18	16	256	250	2650	95	9.8	104.3	3.7	2	1
FOS-19	16	288	250	2970	95	9.8	116.9	3.7	2	1
FOS-22	32	64	410	730	95	16.1	28.7	3.7	4	2
FOS-23	32	96	410	1050	95	16.1	41.3	3.7	4	2
FOS-24	32	128	410	1370	95	16.1	53.9	3.7	4	2
FOS-25	32	160	410	1690	95	16.1	66.5	3.7	4	2
FOS-26	32	192	410	2010	95	16.1	79.1	3.7	4	2
FOS-27	32	224	410	2330	95	16.1	91.7	3.7	4	2
FOS-28	32	256	410	2650	95	16.1	104.3	3.7	4	2
FOS-29	32	288	410	2970	95	16.1	116.9	3.7	4	2
FOS-33	48	96	570	1050	95	22.4	41.3	3.7	6	3
FOS-34	48	128	570	1370	95	22.4	53.9	3.7	6	3
FOS-35	48	160	570	1690	95	22.4	66.5	3.7	6	3
FOS-36	48	192	570	2010	95	22.4	79.1	3.7	6	3
FOS-37	48	224	570	2330	95	22.4	91.7	3.7	6	3
FOS-38	48	256	570	2650	95	22.4	104.3	3.7	6	3
FOS-39	48	288	570	2970	95	22.4	116.9	3.7	6	3
FOS-44	64	128	730	1370	95	28.7	53.9	3.7	8	4
FOS-45	64	160	730	1690	95	28.7	66.5	3.7	8	4
FOS-46	64	192	730	2010	95	28.7	79.1	3.7	8	4
FOS-47	64	224	730	2330	95	28.7	91.7	3.7	8	4
FOS-48	64	256	730	2650	95	28.7	104.3	3.7	8	4
FOS-49	64	288	730	2970	95	28.7	116.9	3.7	8	4
FOS-55	80	160	890	1690	95	35.0	66.5	3.7	10	5
FOS-56	80	192	890	2010	95	35.0	79.1	3.7	10	5
FOS-57	80	224	890	2330	95	35.0	91.7	3.7	10	5
FOS-58	80	256	890	2650	95	35.0	104.3	3.7	10	5
FOS-59	80	288	890	2970	95	35.0	116.9	3.7	10	5

1. LED boards can be controlled via RS232 or RS485 -Serial interface
2. Optional – we can supply LED boards along with Protocol document – This can be directly interfaced with your data device. We can support ASCII Protocol by default. MODBUS and other protocols on request.
3. LAN boards can also be supplied – Optional
4. Each board supplied with 5 meters Communication cable
5. LAN boards are not supplied with any cable – you may connect it to your nearest LAN Port.
6. Install PC software. Use PC software to send data to the LED board.
7. Displays in Any language. (subject to availability of fonts in your PC)
8. Connect multiple displays from one PC
9. LED boards works on 230V AC mains (110V clocks can be quoted for separately)
10. LED boards display in Single colour. The Default supply is always in RED colour. Other colours on request at extra cost.
11. RED colour Brightness is good for viewing both indoors and outdoors.
12. For outdoor displays – cost increases by 18% on base price.
13. Mounting provision – option #1 – Top eye bolts – you can hang it from ceiling. Option # 2 – Side clamps – you can bolt it to your supports.

